

# **Oil Furnaces**

Keeping Families Comfortable for more than 60 years

Airco has the optimal oil furnace solution for you with **Highboy** and **Lowboy** models.



BCL



BFL

HTL

### FEATURING

- ✓ Optional ECM Motor
- ✓ AFUE Up to 85%
- Air Conditioning Ready
- ✓ Up to B₂o Biodiesel Certified
- High Grade Steel Refractory
  Combustion Chamber

#### aircofurnaces.com

#### PN 240009878A Rev. 01/19/24



| 100              | 200   |  |  |
|------------------|---|--|--|
| 77,000 - 154,000 |   |  |  |
| Up to 85%        |   |  |  |
| Rear Breech (5") |   |  |  |
| 37 3/8"          | 39 3/8"   |  |  |
| 20" x 18"        | 20" X 20"   |  |  |
| 20" X 20"        | 20" X 20"   |  |  |
|                  | 77,000 -<br>Up to<br>Rear Bre<br>37 3/8"<br>20" x 18" |  |  |

### **Lowboy Series**

The Lowboy series is capable of achieving up to 85% AFUE efficiency due to its unique heat exchanger design, high performance oil burners and refractory combustion chamber. This results in increased energy savings and lower fuel bills.

Our heat exchangers are constructed of welded steel for added reliability and the large surface area maximizes heat transfer into your home.

Extremely flexible installation with front and rear flue options along with multiple firing rates, burner options, and optional ECM blower motor.



| BFL             | 100               | 200       |  |  |
|-----------------|-------------------|-----------|--|--|
| Btu/h Input     | 77,000 - 154,000  |           |  |  |
| AFUE Efficiency | Up to 85%         |           |  |  |
| Flue Location   | Front Breech (5") |           |  |  |
| Height          | 37 7/16"          | 42"       |  |  |
| Cold Air Return | 20" x 18"         | 20" X 20" |  |  |
| Hot Air Supply  | 20" X 20"         | 22" X 20" |  |  |

#### Features Chimney Vent Burner Options

(B20 Bio-diesel Ready)

- Beckett AFG
- Carlin EZ-1 Select
- **Blower Motor Options** 
  - PSC Direct Drive

• ECM

Other

- Filter:
- BCL / BFL: 20" x 20" x 1"
- Barometric damper
- Durable steel cabinet ensures strength while full fiber-reinforced insulation provides quiet operation. An appliance grade textured finish minimizes fingerprints.
- A/C ready BCL/BFL-100 up to 3 tons BCL/BFL-200 up to 5 tons





### **Highboy Series**

The Highboy series is capable of achieving up to 85% efficiency due to its unique heat exchanger design, high performance oil burners and refractory combustion chamber. This results in increased energy savings and lower fuel bills.

Each Highboy furnace has a completely insulated combustion chamber to provide quiet operation and clean burning performance.

Flexible installation with multiple firing rates, burner options, and optional ECM blower motor.

(up flow only)

| HTL             | 100               | 200       |  |  |
|-----------------|-------------------|-----------|--|--|
| Btu/h Input     | 77,000 - 154,000  |           |  |  |
| AFUE Efficiency | Up to 85%         |           |  |  |
| Flue Location   | Front Breech (5") |           |  |  |
| Height          | 54"               | 60"       |  |  |
| Cold Air Return | 18" x 18"         | 23" x 18" |  |  |
| Hot Air Supply  | 20" X 20"         | 20" X 24" |  |  |



### Features

Chimney Vent Burner Options (B20 Bio-diesel Ready)

- Beckett AFG
- Carlin EZ-1 Select
- **Blower Motor Options** 
  - PSC Direct Drive

• ECM

Other

- Filter: HTL-100 20" x 20" x 2" HTL-200 20" x 25" x 2"
- Barometric damper
- Durable steel cabinet ensures strength while full fiber-reinforced insulation provides quiet operation. An appliance grade textured finish minimizes fingerprints.
- A/C ready HTL-100 up to 3 tons HTL-200 up to 5 tons

# Specifications - BCL, BFL, HTL



| Furnace Model  | BCL-100                   | BCL-200                   | BFL-100                   | BFL-200                   | HTL-100                   | HTL-200                   |
|--|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| Firing Rate<br>(Bold = factory installed)  | 0.55   <b>0.65</b>   0.75 | 0.85   <b>0.95</b>   1.10 | 0.55   <b>0.65</b>   0.75 | 0.85   <b>0.95</b>   1.10 | 0.55   <b>0.65</b>   0.75 | 0.85   <b>0.95</b>   1.10 |
| Input Capacity MBH   | 77   91   105             | 119   133   154           | 77   91   105             | 119   133   154           | 77   91   105             | 119   133   154           |
| Output Capacity MBH  | 65   76   87              | 100   110   127           | 65   76   87              | 100   110   127           | 65   76   87              | 100   110   127           |
| <b>AFUE %</b> (range based on burner selection)                                      | 83 - 85                   | 83 - 85                   | 83 - 85                   | 83 - 85                   | 83 - 85                   | 83 - 85                   |
| A/C Ready  | up to 3 tons              | up to 5 tons              | up to 3 tons              | up to 5 tons              | up to 3 tons              | up to 5 tons              |
| PSC Blower Motor hp<br>Number of Speeds<br>CFM at 0.50" wc<br>(ext. static pressure) | 1/2 hp<br>4<br>1,230      | 3/4 hp<br>4<br>1,730      | 1/2 hp<br>4<br>1,915      | 3/4 hp<br>4<br>2,500      | 1/2 hp<br>4<br>1,200      | 3/4 hp<br>4<br>1,745      |
| ECM Blower Motor hp<br>Number of Speeds<br>CFM at 0.50" wc<br>(ext. static pressure) | 1/2 hp<br>5<br>1,470      | 3/4 hp<br>5<br>2,075      | 1/2 hp<br>5<br>1,550      | 3/4 hp<br>5<br>2,240      | 1/2 hp<br>5<br>1,485      | 3/4 hp<br>5<br>1,770      |
| Height   | 37 3/8"                   | 39 3/8"                   | 37 7/16"                  | 42"                       | 54"                       | 60"                       |
| Width  | 21 1/4"                   | 21 1/4"                   | 21 1/4"                   | 21 1/4"                   | 21 1/2"                   | 24 1/2"                   |
| Depth  | 43 11/16"                 | 45 7/8"                   | 43 1/2"                   | 47 11/16"                 | 24 1/2"                   | 29 1/2"                   |
| Flue Diameter  | 5"                        | 5"                        | 5"                        | 5"                        | 5"                        | 5"                        |
| Supply Plenum Size   | 20" x 20"                 | 20" x 20"                 | 20" x 20"                 | 22" x 20"                 | 20" x 20"                 | 20" x 24"                 |
| Return Plenum Size   | 20" x 18"                 | 20" x 20"                 | 20" x 18"                 | 20" x 20"                 | 18" x 18"                 | 23" x 18"                 |

Specifications subject to change without notice.

## **Flexible Burner Options**

Take advantage of today's modern burner technology. Choose from Beckett or Carlin burners.

### **Beckett Burner**





2201 Dwyer Avenue, Utica, NY 13501 Tel. 800 253 7900 www.ecrinternational.com F.W. WEBB COMPANY

160 Middlesex Turnpike Bedford, MA 01730 781-272-6600

**Carlin Burner** 





All specifications subject to change without notice. ©2024 ECR International, Inc. PN 240009878A REV. [01/19/2024]